WEST Search History

| Hide Items | Restore | Clear | Cancel |

DATE: Sunday, June 12, 2005

Hide?	Set Name	Query	Hit Count
		DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=OR	
☐	L30	L28 and "prevent transmission"	0
☐	L29	L28 same "prevent transmission"	0
☐	L28	"flooding attack" same "time interval"	14
☐	L27	"flooding attack" near "predetermined time interval"	0
☐	L26	"flooding attack" and "predetermined time interval"	3
☐	L25	"flooding attack" same "predetermined time interval"	0
☐	L24	"flooding attack" with "predetermined time interval"	0
☐	L23	"flooding attack" with "predetermined timing interval"	0
☐	L22	L21 and "predetermined time interval"	2
☐	L21	L15 and "flooding attack"	39
☐	L20	L19 and L18	1
☐	L19	L16 and L17	1
☐	L18	at&t.asn.	8622
☐	L17	tewani.in. and kamlesh.in.	16
☐	L16	halasz.in. and sylvia.in.	1
☐	L15	713/201.ccls.	3682
☐	L14	713/200.ccls.	3060
☐	L13	709/229.ccls.	2389
☐	L12	709/227.ccls.	2564
☐	L11	709/224.ccls.	3952
☐	L10	709/225.ccls.	1815
		DB=USPT; PLUR=YES; OP=OR	
☐	L9	L2 and "first connection"	1
☐	L8	L7 and (signal)	1
☐	L7	L6 and (address)	5
☐	L6	L5 and (den$5)	5
☐	L5	L4 and "time interval"	5
☐	L4	L2 and "connection"	17
☐	L3	L2 and "data connection"	0
☐	L2	"flooding attack"	18
☐	L1	"flooding attack" same "host device"	0

Web   Images   Groups   News   Froogle   Local   more »

Google |flooding attack, time interval, synchronization,| Search   Advanced Search
                                                                Preferences

Web Results 1 - 10 of about **17,800** for <u>**flooding attack, time interval, synchronization, signal, IP address**</u>. (

<u>Keeping **Time** on Windows Machines</u>
It's important that the **time** on machines are closely **synchronized**, ... Note that
Windows 2000 only recognizes the first DNS or **IP address** in the "ntp server ...
www.wilsonmar.com/1clocks.htm - 49k - <u>Cached</u> - <u>Similar pages</u>

[PDF] <u>Anomaly detection in **IP** networks - **Signal** Processing, IEEE ...</u>
File Format: PDF/Adobe Acrobat - <u>View as HTML</u>
flooding attacks. SYN **flooding attacks** capitalize ... network measurements, **IP**
QoS, **time** series analysis,. and **signal** detection theory. ...
www.eecs.umich.edu/~zmao/ eecs589/papers/AnomalyDetection.pdf - <u>Similar pages</u>

<u>Solaris - Tuning Your TCP/IP Stack</u>
This value is interesting considering SYN **flood attacks** on your server. ...
Each **IP address** is assumed to be a logical interface. ...
www.sean.de/Solaris/soltune.html - 101k - Jun 11, 2005 - <u>Cached</u> - <u>Similar pages</u>

[PDF] <u>Distinguishing between single and multi-source **attacks** using ...</u>
File Format: PDF/Adobe Acrobat - <u>View as HTML</u>
the complete **IP address** space. Many **attack** tools. use reflection techniques,
subnet spoofing, or do ... tight **time synchronization** between attacking hosts ...
www.isi.edu/~hussain/pubs/Hussain04b.pdf - <u>Similar pages</u>

[PDF] <u>Distributed Denial of Service</u>
File Format: PDF/Adobe Acrobat
the specified **IP addresses** for a period of **time** (default is 120 seconds, or 1 – 1999
... All of the **attacks** utilize spoofing of **IP addresses**. ...
www.ciac.org/ciac/documents/ CIAC-2319_Distributed_Denial_of_Service.pdf - <u>Similar pages</u>

[PDF] <u>COPING WITH OVERLOAD ON THE NETWORK **TIME** PROTOCOL PUBLIC SERVERS</u>
File Format: PDF/Adobe Acrobat - <u>View as HTML</u>
Annual Precise **Time** and **Time Interval** (PTTI) Meeting. 12. destination **IP address**
and use a load-sharing scheme similar to USNO and NIST to distribute ...
tycho.usno.navy.mil/ptti/ptti2004/paper2.pdf - Jun 11, 2005 - <u>Similar pages</u>

[DOC] <u>DDoS **Attacks**</u>
File Format: Microsoft Word 2000 - <u>View as HTML</u>
The following **attack** parameters are controllable: victims **IP addresses**, ...
The timeStamp is needed for calculations of **time intervals** between several ...
www-comnet.technion.ac.il/~cn1w03/ docs/DDoS_MidSubmission2_final2.doc - <u>Similar pages</u>

[PDF] <u>15-441 Spring 2004 - Final Name: _____ Andrew ID ...</u>
File Format: PDF/Adobe Acrobat - <u>View as HTML</u>
the host name corresponding to the destination **IP address** for the packet ...
a) A SYN **flood attack** with randomly spoofed source **addresses** against 23.45.6.7 ...
www-2.cs.cmu.edu/~srini/ 15-441/S05/exams/2004sp_final.pdf - <u>Similar pages</u>

[PDF] <u>Perimeter-Based Defense against High Bandwidth DDoS **Attacks**</u>
File Format: PDF/Adobe Acrobat - <u>View as HTML</u>
perimeter-based **IP** traceback, it can determine the **addresses** of the edge routers

... Under the **attack**, the victim **signals** router A to initiate the defense. ...
www.cise.ufl.edu/~sgchen/papers/TPDS2005.pdf - <u>Similar pages</u>

[PDF] <u>Collaborative Defense against Periodic Shrew DDoS **Attacks** in ...</u>
File Format: PDF/Adobe Acrobat - <u>View as HTML</u>
constant **time interval**, which in our case is 1 ms. ... Although the source **IP**
**addresses** are. generally spoofed in **attack** packets, it is safe to use the ...
gridsec.usc.edu/files/TR/ ACMTISSEC-LowRateAttack-May3-05.pdf - <u>Similar pages</u>

Gooooooooooogle ►
Result Page: **1** <u>2</u> <u>3</u> <u>4</u> <u>5</u> <u>6</u> <u>7</u> <u>8</u> <u>9</u> <u>10</u>   **Next**

Free! Get the Google Toolbar. <u>Download Now</u> - <u>About Toolbar</u>

Google ▾ | Search ▾ | 377 blocked | Check ▾ | AutoLink ▾ | AutoFill

flooding attack, time interval, synchr | Search

<u>Search within results</u> | <u>Language Tools</u> | <u>Search Tips</u> | <u>Dissatisfied? Help us improve</u>

<u>Google Home</u> - <u>Advertising Programs</u> - <u>Business Solutions</u> - <u>About Google</u>

©2005 Google